

Tohatsu - MFS 5 DS L

£ 1,023

📍 Lymington, South East



SAL Marine Ltd
www.salmarine.com

01590 679588

- Outboard Petrol Engines
- United Kingdom
- 5

The 5hp short & long shaft models are now available with either an internal 1.15 litre fuel tank (5CD model) or with an external 12 litre fuel tank (5CS model).

Tohatsu 4-stroke 5HP benefits:

Light and compact!

Front mounted shift lever, an industry first in its class!

Designed with proven technology

Greatly reduced vibration for smooth and stable running at all speeds

Greatly reduced induction noise for a quieter ride

Ultra-low emission, EU and CARB 3-Star rating approved

5 Year limited warranty

High performance and easy operation:

Digital CD ignition for easier engine starting, quicker throttle response and smoother trolling

Recoil starter with larger reel making manual starting fast and easy

Shallow water drive

6 trim positions

Adjustable steering friction for reducing steering effort

New longer tiller handle (110mm extension)

Newly designed holding grip and larger carrying handle

Fundamentals for user convenience and reliability:

Through-the-prop exhaust for a quieter ride

Thermostatically controlled cooling system for consistent engine temperature

Stainless steel water pump housing liner for outstanding durability

High grade marine aluminum alloy that provides the ultimate protection against corrosion

Zinc coating on internal water passages for superior corrosion resistance
12 litre fuel tank including fuel fittings and fuel line
Warning and protection:

Low oil pressure indicator
Safety lanyard (an essential protection feature standard on all Tohatsu outboards)
Start-in-gear protection for safer engine starting
Over-rev. limiter

Specifications:

Maximum output 5HP (3.68 KW)

Maximum operation range 4500-5500 rpm

Fuel Consumption at W.O.T 1.7 L/Hr

Number of cylinder 1

Bore x Stroke 59 x 45 mm

Displacement 123 cc

Engine lubrication system Trochoid pump

Starting System Manual or Electric starter

Spark plug NGK DCPR6E

Ignition timing BTDC0° - BTDC25°

Alternator output 12V, 60W 5A

Volume of engine oil API Standard (SG, SH, SJ) SAE 10W-40

Engine oil capacity 0.45L w/ Filter change

Fuel tank capacity 12L or Internal 1.15L

Speed control Twist Grip Type

Gear reduction ratio 2.15

Emission compliance EU & CARB 3-Star

To see this ad online, go to boatsandoutboards.co.uk and search for **BU7138FE3**



SAL MARINE

HONDA
MARINE

VOLVO
PENTA

 **SUZUKI**
MARINE

 **TOHATSU**
Outboards

 **vetus**

 **nanni**
energy in blue

 **HIGHFIELD**

**FMT**
PREMIUM BOATS

Sales, Parts, Repairs, Servicing

01590 679588
www.SALMARINE.com

SAL Marine
Mill Lane
Lymington
SO41 9AZ
